



# Food Parry light

Non Standard rubber hose

**Application:** Hardwall hose suitable for suction and delivery of fatty foods at 100%.

**Temperature range:** -15°C (-5°F)+90°C (+194°F).

### Construction

**Tube:** White, smooth, food quality NBR rubber compound in accordance to below mentioned FDA specifications.

**Reinforcement** high strength synthetic cord and helix wire.

**Cover:** blue, smooth (wrapped finish), synthetic rubber.

**Standards:** ○ F.D.A. title 21

**Sanification:** max. 110°C for max. 15 minutes with steam; max. 50°C for a few minutes with 1% peracetic acid, 2% phosphoric acid, 5% caustic soda.

Code	Inside diameter mm	Outside diameter mm	Working pressure bar	Burst pressure (theoretical) bar	Weight (nominal) Kg/m
1024531	25	34	10	30	0,70
1425340	38	48	10	30	1,20
1200666	51	62	10	30	1,70
1229214	63.5	77	10	30	2,65
1428004	76	90	10	30	3,30
1333852	102	117	10	30	4,64

max manufactured length	Up to ID
m	mm
60	102

#### **Food Parry light**

*L'Ivg Colbachini Spa si riserva di variare in qualsiasi momento i dati sopra riportati nell'ottica del continuo miglioramento del prodotto*

*Data di emissione:16.09.09*

**COPIA IN DISTRIBUZIONE NON CONTROLLATA**

Ivg Colbachini Spa, in view of the continuous product improvement, reserves the right to modify at any time the above mentioned data.

**UPDATE DISTRIBUTION OF THIS COPY IS UNCONTROLLED**